

[Inicio](#) » [Productos](#) » [LAN Inalámbrica](#) » [Wireless AC](#) » [Archer C20i](#)

AC1750

802.11ac

Router Gigabit Inalámbrico de Banda Dual AC1750



AC750 Wireless Dual Band Router Archer C20i

Prestaciones:

- Supports 802.11ac standard - the next generation of Wi-Fi
- Simultaneous 2.4GHz 300Mbps and 5GHz 433Mbps connections for 733Mbps of total available bandwidth
- Stable omnidirectional signal and superior wireless coverage
- USB port - share a printer locally and files & media with networked devices or remotely via FTP server



Visión General

Características

Especificaciones

Descargas



CARACTERÍSTICAS DE HARDWARE	
Interfaces	4 10/100 LAN ports 1 10/100 WAN port 1 USB 2.0 port
Botones	WPS/Reset Button Wireless On/Off Button Power On/Off Button
Fuente de alimentación externa	12VDC /1A
Dimensiones (W X D X H)	4.44 x 2.36 x 6.73 in. (113 x 60 x 171mm)
Antenas	3 internal antennas

CARACTERÍSTICAS INALÁMBRICAS	
Estándares Inalámbricos	IEEE 802.11ac/n/a 5GHz IEEE 802.11b/g/n 2.4GHz
Frecuencia	2.4GHz and 5GHz
Tasas de transferencia	5GHz: Up to 433Mbps 2.4GHz: Up to 300Mbps
PIRE	<20dBm(EIRP)
Sensibilidad de Recepción	5GHz 11a 6Mbps: -91dBm, 11a 54Mbps: -74dBm 11ac HT20: -66dBm, 11ac HT40: -64dBm, 11ac HT80: -61dBm, 11n HT20: -71dBm, 11n HT40: -69dBm 2.4GHz 11g 54M: -74dBm 11n HT20: -72dBm, 11n HT40: -69dBm
Funciones Inalámbricas	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Seguridad Inalámbrica	64/128-bit WEP,WPA / WPA2,WPA-PSK/ WPA2-PSK encryption

CARACTERÍSTICAS DE SOFTWARE	
Tipo de WAN	Dynamic IP/Static IP/PPPoE/ PPTP(Dual Access)/L2TP(Dual Access)/BigPond

Productos relacionados



Router Gigabit de Banda Dual
Inalámbrico AC750
Archer C2

Preguntas más Frecuentes

Troubleshooting information for
your product

CARACTERÍSTICAS DE SOFTWARE	
DHCP	Server, Client, DHCP Client List, Address Reservation
Calidad de Servicio	WMM, Bandwidth Control
Port Forwarding	Virtual Server, Port Triggering, UPnP, DMZ
DNS Dinámico	DynDns, Comexe, NO-IP
VPN	PPTP, L2TP, IPSec
Control de acceso	Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall de seguridad	DoS, SPI Firewall IP Address Filtering/MAC Address Filtering/Domain Filtering IP and MAC Address Binding
Protocolos	Supports IPv4 and IPv6
USB compartido	Support Samba(Storage)/ FTP Server/Media Server/Printer Server
Gestión	Access Control Local Management Remote Management
Red de Invitados	2.4GHz guest network x 1 5GHz guest network x 1
OTROS	
Certificaciones	CE, FCC, RoHS
Contenido del Paquete	AC750 Wireless Dual Band Router Archer C20i Power Supply Unit Resource CD Ethernet Cable Quick Installation Guide
Requisitos del sistema	Windows 8/7/Vista/XP, Mac OS or Linux-based operating system
Factores ambientales	Operating Temperature: 0°C~40 °C (32 °F~104°F) Storage Temperature: -40°C~70 °C (-40 °F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing